

Technical data sheet HU243

Specification HUB 2 screen low,part.wall I suit.for HUB2 dec sti

Dimensions in mm

Packaging data	Total:	H:	1350
		W (no ArmR):	1625
	D:	850	
	Weight:	kg	
	Volume:	m³	



Basic equipment

Benefit

Frame	Aluminium profile frame, 1625 x 1350 x 55 mm (W x H x D), in black or white.	Attractive look.
Cover	Covered with laminated fabric on both sides, decorative seams on one side.	Attractive look.
Cover materials	Various fabric qualities in various colours.	Individual design.
Glides	Glides with levelling of up to 10 mm.	Firm contact with the floor and height adjustment.
Materials used	HDF panels all round. All materials are unmixed and recyclable.	Improve the screen's stability. Environmentally friendly.
Standards	GS-symbol for tested safety. Tested for absence of harmful substances.	High level of safety.
Certification	Quality management system DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Occupational Health and Safety Management System ISO 45001:2018, EcoVadis Gold.	High-quality product.
Warranty and returns	10 year warranty according to our current warranty conditions.	Quality guaranteed to last for entire product life.

Disassembly instructions are available upon request for any interstuhl product

Technical data sheet HU243

Specification HUB 2 screen low,part.wall I suit.for HUB2 dec sti

Dimensions in mm

Total:	H:	1350
	W (no ArmR):	1625
	D:	850

Packaging data	Weight:	kg
	Volume:	m³



Options

Benefit

Acoustic performance	Sound-absorbing polyester panels integrated across entire surface, 50 mm thick.	For perfect sound absorption and insulation.
Ambient light	Ambient light/transformer LED lighting fitted to inside of surrounding aluminium profile. Light intensity and warmth can be controlled with supplied remote control or via an app.	Indirect lighting without the need for additional lamps.

Disassembly instructions are available upon request for any interstuhl product