





F7543031 Matte Black

To-Tie T3 NEW

Designed by Guglielmo Poletti, 2022




10W - 495lm - 2700K - CRI> 90

Designed by Guglielmo Poletti Table lamp providing diffused light. Clear glass cylindrical lamp body available in multiple sizes. The handle is made of aluminum and also acts as a light emitter. Multi-led diffuser in specially designed white polycarbonate to avoid the Multi Shadow effect and dazzle. High efficiency LED source with a lifetime of more than 50.000 hours. Electric cable of useful length 180 cm, covered in black fabric and equipped with dimmer switch for ON/OFF and adjustment of the light flow between 10-100%. Plug-in power supply with interchangeable plugs. To-Tie is a future-proof lamp as no glue is used to assemble its different parts. The product can therefore be separated, replaced individually, and recycled separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607047637
Mounting	Table
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	10
System flux (lm)	495

Physical

Colour	Matte Black
Net weight (kg)	2.7
Package volume (m3)	0.05
IP internal	20
H2O stop	No







Photometric Files

LDT / IES



Technical Drawings

2D	⊥ ZIP
3D	⊥ ZIP



















https://professional.flos.com/en/global/product/to-tie-t3-f7543031/

F7543031

Schematic light drawing



Beam	Beam Angle:	
h(m)	E(lx)	D(m)
1	187	2.53
2	47	5.07
3	21	7.60
4	12	10.13
5	7	12.66

Luminous flux 495 lm

300	5	7	12
luminaire			

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90

Electrical

Insulation class	III	
Frequency (Hz)	50/60	
Main voltage (Vac)	24	
LED voltage Vf (Vdc)	24.00	
LED current (mA)	500	
Driver	Remote included	
Dimmable	Yes	
Dimming type	Electronic 24V	
Dimming interface	Dimmer Integrated	
Plug type	Type G, Type A, Type	

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by an end-



Replaceable control gear by an end-user



D1. Black plug assembly kit & 24V RF3320100 driver



RF3320100

Black plug assembly kit & 24V driver