

Technical data sheet HU155

Specification HUB screen high, partition wall high w.dec.stitch

Dimensions in mm

Total:	H:	1900
	W (no ArmR):	1000
	D:	425

Packaging data	Weight:	kg
	Volume:	m³



Basic equipment

Benefit

General	Sound-absorbing polyester panels integrated across entire surface, 50 mm thick.	Perfect sound absorption and insulation.
Frame	Aluminium profile frame. 1000 x 1900 x 55 mm (W x H x D), in black or white.	Attractive look.
Cover	Covered with laminated fabric on both sides, decorative seams on one side.	Can be used as a notice board.
Cover materials	Various fabric qualities in various colours.	Individual design.
Metal parts	Steel base, powder-coated in black or white.	Optimum stability.
Inlaid material	All materials are unmixed and recyclable.	Environmentally friendly.
Standards	GS-symbol for tested safety. Tested for absence of harmful substances.	High level of safety.
Certification	Quality management system DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Occupational Health and Safety Management System ISO 45001:2018, EcoVadis Gold.	High-quality product.
Warranty and returns	10 year warranty according to our current warranty conditions.	Quality guaranteed to last for entire product life.

Disassembly instructions are available upon request for any interstuhl product

Technical data sheet HU155

Specification HUB screen high, partition wall high w.dec.stitch

Dimensions in mm

Total:	H:	1900
	W (no ArmR):	1000
	D:	425

Packaging data	Weight:	kg
	Volume:	m ³



Options

Benefit

Connecting element	Connecting element to link several individual screens, in black or white.	Flexible extension.
Practical hook	Practical steel hook in black or white.	For hanging up jackets, flip charts or whiteboards.
Whiteboard	Whiteboard incl. 2 practical hooks in black or white.	Additional function.

Disassembly instructions are available upon request for any interstuhl product