

m o o o i

Gravity Chandelier

PAUL COCKSEGE



The Gravity Chandelier by Paul Cocksedg re-imagines the chandeliers of the past. Inspired by changing rigidity to elasticity. The Gravity Chandelier is the definition of a modern chandelier. At first glance, it doesn't reveal its flexibility and cleverness; It takes a second look to unravel its mystery. With its flexible arms, you define the chandelier's diameter and choose where the light travels, but the suspended elements create natural curves shaped by gravity. The Gravity Chandelier comes in two sizes, after the number of arms, Gravity Chandelier 5 and Gravity Chandelier 7.

Detailing



The Gravity Chandelier lets you choose its diameter and where the light travels.


Colours



Black

Gravity Chandelier / 5

Dimensions



Product

WIDTH 127cm | 50"
HEIGHT 90cm | 35.4"
DEPTH 127cm | 50"
DIAMETER 127cm | 50"
WEIGHT NETTO 6kg | 13.23lbs

Packaging

WIDTH 67.5cm | 26.6"
HEIGHT 45.5cm | 17.9"
CUBAGE 0.21m³ | 7.32ft³
LENGTH 67.5cm | 26.6"
WEIGHT 10kg | 22.05lbs

Technical CE / cULus

ADDITIONAL

Compatible with our Wireless Wall Switch, for quick and easy dimming that gives you full control over the light output.

MATERIAL

Facetted glass with powder coated steel light unit, ultra-thin suspension wire and braided flat cable

ENERGY LABEL

Energy Label A

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

5

INPUT VOLTAGE

120-250

FREQUENCY

50/60

MAX POWER CONSUMPTION

18W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

CANOPY

Matching steel cylinder

CHROM X

0.46

CHROM Y

0.4

COLOUR TEMPERATURE

2614 K

CRI

89

LIGHT DIRECTION

All directions

LIGHT OUTPUT

1025 lm

EEL
0.23

EFFICIENCY
56.94 lm/W

DIMMING & LIGHTING CONTROL


DALI dt6, Push / Pulse dim on Line Voltage, Wireless Wall Switch

See last page for more information about the dimming possibilities.



Gravity Chandelier / 7

Dimensions



Product

WIDTH 127cm | 50"
HEIGHT 90cm | 35.4"
DEPTH 127cm | 50"
DIAMETER 127cm | 50"
WEIGHT NETTO 7kg | 15.43lbs

Packaging

WIDTH 67.5cm | 26.6"
HEIGHT 45.5cm | 17.9"
CUBAGE 0.21m³ | 7.32ft³
LENGTH 67.5cm | 26.6"
WEIGHT 12kg | 26.46lbs

Technical CE / cULus

ADDITIONAL

Compatible with our Wireless Wall Switch, for quick and easy dimming that gives you full control over the light output.

MATERIAL

Faceted glass with powder coated steel light unit, ultra-thin suspension wire and braided flat cable

ENERGY LABEL

Energy Label A

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

7

INPUT VOLTAGE

120-250

FREQUENCY

50/60

MAX POWER CONSUMPTION

25W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

CHROM X

0.46

COLOUR TEMPERATURE

2614 K

LIGHT DIRECTION

All directions

EEL

0.24

DIMMING & LIGHTING CONTROL

DALI dt6, Push / Pulse dim on Line Voltage, Wireless Wall Switch

See last page for more information about the dimming possibilities.

**CANOPY**

Matching steel cylinder

CHROM Y

0.4

CRI

89

LIGHT OUTPUT

1434 lm

EFFICIENCY

57.36 lm/W

Dimming & Lighting Control

DALI dt6

The luminaire is dimmable by integrating it into a DALI network. This is an universal and professional standard in home automation systems with endless control possibilities and ease. We advise to hire a professional to integrate the luminaire into your DALI network.

Compatible models: 5 CE, 5 cULus, 7 CE, 7 cULus

Push / Pulse dim on Line Voltage

The luminaire is dimmable by using an external momentary switch or pushbutton switch. The switch is usually mounted on an existing wall socket. In some cases a Phase or Control wire needs to be added to your home's wiring. The switch should be suitable for use with line voltage and of the type 'normal off - momentary on'. The luminaire dims perfectly when the switch makes and holds contact. A short press switches between on and off.

Compatible models: 5 CE, 5 cULus, 7 CE, 7 cULus

Wireless Wall Switch

With our Wireless Wall Switch, you'll have full control over your Moooi lighting design with one touch. Our Wireless Wall Switch comprises two components, a wall switch and radio device to put in the canopy of your Moooi lighting design. The wall switch can be integrated in System 55 or Decora style wall switches. The Wireless Wall Switch communicates via Bluetooth with the radio device in the luminaires canopy. Within moments you can enjoy full and fluent dimming, all the way to dark.

Compatible models: 5 CE, 5 cULus, 7 CE, 7 cULus
