## moooi

# The Party Wall Lamp

KRANEN/GILLE



The Party' is inspired by a clan of strong, captivating personalities. Their casted ceramic faces bring to light our fascination with secrets, family dynamics and intrigue. If seen together, as a splendid party, they brighten up the stage with their cool playfulness. Yet behind the lamps' composed façades a mischievous side seeps through and touches our imagination.

### Detailing



The lamps share the same basic tactile feel, a subtle roughness given by the granular ceramic finish, but are distinguished by their individual style.

### **Colours**



Grey

### The Party Wall Lamp / Bert

**Dimensions** 

16cm | 6.3"

| 11cm | 4.3" | 22cm | 6 | | |

Product

**WIDTH** 16cm | 6.3" **HEIGHT** 22cm | 8.7" **DEPTH** 11cm | 4.3"

**WEIGHT NETTO** 0.5kg | 1.1lbs

**Packaging** 

width  $31.5 \text{cm} \mid 12.4$ " Height  $31.5 \text{cm} \mid 12.4$ " cubage  $0.02 \text{m}^3 \mid 0.72 \text{ft}^3$  Length  $20.5 \text{cm} \mid 8.1$ "

**weight** 3kg | 6.61lbs

Technical CE

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

**LED** 

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

**INPUT VOLTAGE** 220-240

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

**CRI** 85

LIGHT OUTPUT

77 Im

**DIMMING & LIGHTING CONTROL** 

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.

 $\epsilon$ 

Technical cULus

Ceramic, Enogobio Finish, Alumminum, Brass knob

**ENERGY LABEL** 

Energy Label B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

**CABLE COLOUR** 

Black

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

**DIMMING & LIGHTING CONTROL** 

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

110-120

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CABLE LENGTH

15cm | 5.9"

CRI

85

LIGHT OUTPUT

77 Im

### The Party Wall Lamp / Coco

**Dimensions** 

18cm | 7.1"







11cm | 4.3"

Product

**width** 18cm | 7.1" **HEIGHT** 22cm | 8.7"

**DEPTH** 11cm | 4.3"

**weight netto** 0.5kg | 1.1lbs

Packaging

**WIDTH** 31.5cm | 12.4"

**неіднт** 31.5cm | 12.4"

**CUBAGE**  $0.02\text{m}^3 \mid 0.72\text{ft}^3$ 

**LENGTH** 20.5cm | 8.1"

**WEIGHT** 3kg | 6.61lbs

Technical CE

Ceramic, Enogobio Finish, Alumminum, Brass knob

**ENERGY LABEL** 

Energy Label B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

**COLOUR TEMPERATURE** 

2700 K

LIGHT DIRECTION

**DIMMING & LIGHTING CONTROL** 

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.

 $\epsilon$ 

Technical cULus

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

**ENERGY LABEL**Energy Label B

0,

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

220-240

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CRI

85

LIGHT OUTPUT

77 Im

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

110-120

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CABLE LENGTH

15cm | 5.9"

CRI

85

MOOOI.COM

77 Im

#### **DIMMING & LIGHTING CONTROL**


Mains, Trailing edge, Reverse phase


See last page for more information about the dimming possibilities.



### The Party Wall Lamp / Glenn

**Dimensions** 





Product

**widtн** 17cm | 6.7" **HEIGHT** 22cm | 8.7" **DEPTH** 10cm | 3.9" **WEIGHT NETTO** 0.5kg | 1.1lbs Packaging

**widtн** 31.5cm | 12.4" **HEIGHT** 31.5cm | 12.4" **CUBAGE**  $0.02\text{m}^3 \mid 0.72\text{ft}^3$ **LENGTH** 20.5cm | 8.1" **WEIGHT** 3kg | 6.61lbs

Technical CE

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

**ENERGY LABEL** 

Energy Label B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

**COLOUR TEMPERATURE** 

2700 K

LIGHT DIRECTION

**INSTALLATION REQUIRED** 

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE 220-240

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CRI 85

LIGHT OUTPUT

77 Im

#### **DIMMING & LIGHTING CONTROL**

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



Technical cULus

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL INSTALLATION REQUIRED

Energy Label B Yes

LIGHTSOURCE TYPE LIGHTSOURCE INCLUDED

LED

NUMBER OF LIGHTSOURCES INPUT VOLTAGE

110-120

FREQUENCY MAX POWER CONSUMPTION

50/60 6W

LAMPHOLDER LIFETIME

LED (Solid state) 50000 hours

CABLE COLOURCABLE LENGTHBlack15cm | 5.9"

COLOUR TEMPERATURECRI2700 K85

LIGHT DIRECTION LIGHT OUTPUT

77 lm

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



### The Party Wall Lamp / Ted

**Dimensions** 

16cm | 6.3"

 $\Box$ 

10cm | 3.9" 22cm | 8.9"

Product

**WIDTH** 16cm | 6.3" **HEIGHT** 22cm | 8.7" **DEPTH** 10cm | 3.9"

**WEIGHT NETTO** 0.5kg | 1.1lbs

**Packaging** 

width  $31.5 \text{cm} \mid 12.4$ "

Height  $31.5 \text{cm} \mid 12.4$ "

Cubage  $0.02 \text{m}^3 \mid 0.72 \text{ft}^3$ Length  $20.5 \text{cm} \mid 8.1$ "

**weight** 3kg | 6.61lbs

Technical CE

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

**LED** 

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

**INPUT VOLTAGE** 220-240

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

**CRI** 85

LIGHT OUTPUT

77 Im

**DIMMING & LIGHTING CONTROL** 

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.

 $\epsilon$ 

Technical cULus

Ceramic, Enogobio Finish, Alumminum, Brass knob

**ENERGY LABEL** 

Energy Label B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

**CABLE COLOUR** 

Black

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

**DIMMING & LIGHTING CONTROL** 

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

110-120

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CABLE LENGTH

15cm | 5.9"

CRI

85

LIGHT OUTPUT

77 Im

### The Party Wall Lamp / Mayor


**Dimensions** 

17cm | 6.7"









Product

**WIDTH** 17cm | 6.7" **HEIGHT** 22cm | 8.7"

**DEPTH** 10cm | 3.9"

**weight netto** 0.5kg | 1.1lbs

Packaging

**WIDTH** 31.5cm | 12.4"

неіснт 31.5ст | 12.4"

**CUBAGE**  $0.02\text{m}^3 \mid 0.72\text{ft}^3$ 

**LENGTH** 20.5cm | 8.1"

**WEIGHT** 3kg | 6.61lbs

Technical CE

Ceramic, Enogobio Finish, Alumminum, Brass knob

**ENERGY LABEL** 

Energy Label B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

**COLOUR TEMPERATURE** 

2700 K

LIGHT DIRECTION

**DIMMING & LIGHTING CONTROL** 

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.

 $\epsilon$ 

Technical cULus

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

**ENERGY LABEL**Energy Label B

0,

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

220-240

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CRI

85

LIGHT OUTPUT

77 Im

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

110-120

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CABLE LENGTH

15cm | 5.9"

CRI

85

MOOOI.COM

#### LIGHT OUTPUT

77 lm

#### DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



## Dimming & Lighting Control

### Mains, Trailing edge, Reverse phase

The luminaire is dimmable by using an external Electronic Low Voltage dimmer. The dimmer is usually mounted on an existing wall socket and there is no need to change your home's wiring. On the dimmer it should show that it is a LED dimmer, suitable for 5 Watts or lower and C-type capable. Dimming is less fluent and can come with some flicker, a beep or a buzz.

Compatible models: Bert CE, Bert cULus, Coco CE, Coco cULus, Glenn CE, Glenn cULus, Ted CE, Ted cULus, Mayor CE, Mayor cULus