

m o o o i

Prop Light Floor

BERTJAN POT



"We have round lights, we have straight lights. We have them with lights on one side, we have them with lights on two sides. You can hang them high, low, horizontally, vertically or even hang them in an angle. Put them on the floor, hang them on your wall or down from the ceiling. We find it very hard to imagine an interior where this prop is not in place" - Bertjan Pot

Detailing



A theatrical, extravagant lamp that can be place on the floor. Its bubbly form and pure spirit brightens up any kind of environment.

Colours

2000K
Warm White

2700K
Soft White


Prop Light Floor / Vertical

Dimensions

25cm | 9.8"



107cm | 42.1"



Product

WIDTH 25cm | 9.8"
HEIGHT 107cm | 42.1"
DEPTH 25cm | 9.8"
WEIGHT NETTO 8kg | 17.64lbs

Packaging

WIDTH 30cm | 11.8"
HEIGHT 30cm | 11.8"
CUBAGE 0.12m³ | 4.23ft³
LENGTH 133cm | 52.4"
WEIGHT 10kg | 22.05lbs

Technical CE

ADDITIONAL

The Proplight is available in two colour temperatures: 2000K or 2700K.

MATERIAL

HIPS housing, PMMA light guide, glass bulbs

ENERGY LABEL

Energy Label A

LIGHTSOURCE INCLUDED

Yes

SHAPE

Linear

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

CABLE LENGTH

250cm | 98.4"

CRI

80

LIGHT OUTPUT

499 lm

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

18

INPUT VOLTAGE

110-240

MAX POWER CONSUMPTION

10.3W

LIFETIME

50000 hours

PLUG TYPE

Europlug (Type-C)

SWITCH

In line on/off switch

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Integrated dimmer

See last page for more information about the dimming possibilities.



Technical cULus

ADDITIONAL

The Proplight is available in two colour temperatures: 2000K or 2700K.

MATERIAL

HIPS housing, PMMA light guide, glass bulbs

ENERGY LABEL

Energy Label A

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

18

SHAPE

Linear

INPUT VOLTAGE

110-240

FREQUENCY

50/60

MAX POWER CONSUMPTION

10.3W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

PLUG TYPE

US plug (Type A)

CABLE LENGTH

250cm | 98.4"

SWITCH

In line on/off switch

CRI

80

LIGHT DIRECTION

All directions

LIGHT OUTPUT

499 lm

DIMMING & LIGHTING CONTROL

Integrated dimmer


See last page for more information about the dimming possibilities.





Prop Light Floor / Round

Dimensions

73cm | 28.7"



32cm | 12.6"



82cm | 32.3"

Product

WIDTH 73cm | 28.7"

HEIGHT 82cm | 32.3"

DEPTH 32cm | 12.6"

WEIGHT NETTO 10kg |
22.05lbs

Packaging

WIDTH 88cm | 34.6"

HEIGHT 34cm | 13.4"

CUBAGE 0.27m³ | 9.4ft³

LENGTH 89cm | 35"

WEIGHT 15kg | 33.07lbs

Technical CE

ADDITIONAL

The Proplight is available in two colour temperatures: 2000K or 2700K.

MATERIAL

HIPS housing, PMMA light guide, glass bulbs

ENERGY LABEL

Energy Label B

LIGHTSOURCE INCLUDED

Yes

SHAPE

Disc

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

CABLE LENGTH

250cm | 98.4"

CRI

80

LIGHT OUTPUT

1079 lm

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

48

INPUT VOLTAGE

110-240

MAX POWER CONSUMPTION

21W

LIFETIME

50000 hours

PLUG TYPE

Europlug (Type-C)

SWITCH

In line on/off switch

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Integrated dimmer

See last page for more information about the dimming possibilities.



Technical cULus

ADDITIONAL

The Proplight is available in two colour temperatures: 2000K or 2700K.

MATERIAL

HIPS housing, PMMA light guide, glass bulbs

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

48

SHAPE

Disc

INPUT VOLTAGE

110-240

FREQUENCY

50/60

MAX POWER CONSUMPTION

21W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

PLUG TYPE

US plug (Type A)

CABLE LENGTH

250cm | 98.4"

SWITCH

In line on/off switch

CRI

80

LIGHT DIRECTION

All directions

LIGHT OUTPUT

1079 lm

DIMMING & LIGHTING CONTROL

Integrated dimmer

See last page for more information about the dimming possibilities.



Dimming & Lighting Control

Integrated dimmer

Compatible models: Vertical CE, Vertical cULus, Round CE, Round cULus
